

Ambu® WhiteSensor WS-00-S/RT

Lyhytaikainen valvontaelektrodi



Ominaisuudet

- Joustavaa vaahtomuovia
- Röntgen/MRI negatiivinen
- Neppariilitin elektrodin keskellä
- Kiinteä pasta
- Koko 40 x 36 mm
- Ag/Ag Cl -sensori
- Ei sisällä lateksia
- Pakkauskoot: 50/600/7200

Elektrodi lyhytaikaiseen valvontaan. Röntgen- ja MRI-yhtensopiva. Hiilikuituneppari elektrodin keskellä. Miellyttävää vaahtomuovia.

Ambu A/S

PL 27
02211 Espoo
FINLAND
Puh. 09-801 9100
www.ambu.com

WhiteSensor

Ambu
Ideas that work for life

Specifications

Dimensions	
Electrode size (W x L in mm)	36 x 40
Skin contact size (W x L in mm)	36 x 40
Adhesive area (in mm ²)	857
Height excluding connector/wire (in mm)	1,1
Sensor	
Sensor material	Silver/silver chloride
Gel system	Solid
Sensor area (in mm ²)	79
Gel area/measuring area (in mm ²)	201
Electrical data (ANSI/AAMI)	
AC impedance - typical	150 Ω
DC offset voltage - typical	1 mV
Defibrillation overload recovery - typical	12 mV
Rate of change of polarization potential - typical	0.3 mV/s
Combined offset instability and internal noise	9 µV
Bias current tolerance (over 8 hours)	5 mV
Environment	
PVC-free electrode	Yes
Electrode not made with natural rubber latex	
PVC-free packaging	Yes
X-Ray & MRI	
Radiolucent	Yes
MR Conditional	Yes**
Shelf life	
Opened pouches	30 days
Unopened pouches	24 months*

*from date of production

Materials

Electrode	
Bio-compatible	Yes
Sensor	Silver/silver chloride (Ag/AgCl)
Outer carrier	Polyethylene foam (PE)
Outer adhesive	Polyacrylate
Connector (stud)	Carbon
Liner	Polyester (PET)

Standard Packaging	
Quantity/pouch	50
Quantity/box	600/7200
Minimum sales	7200

Options	
Connectors	S
Pre-wired	-
Pre-wired connectors	-

Precaution	
Single use only	

Available configurations

Reference number	Units/card	Units/pouch	Units/inner box	Units/outer box
WS-00-S/RT/50	1	50	600	7200

** Static magnetic field of 1.5 Tesla and 3 Tesla only. Maximum spatial gradient field of 25,000 Gauss/cm or 250 Tesla/m. Maximum whole body averaged specific absorption rate (SAR) of 2 W/kg for 15 minutes of scanning.

- Product
- WS-00-S Wire length (cm)
- Connector

Ambu A/S
 Baltorpbakken 13
 DK - 2750 Ballerup
 Denmark
 Tel. +45 7225 2000
 Fax +45 7225 2053
 www.ambu.com